AMENDMENT TO THE CLAIMS

Please amend the claims as follows. This listing will replace all prior versions and listings of claims in the Application. Claims 7-13 and 17-20 have been amended. Claim 1-6 have been cancelled. New claims 21-26 have been added.

1-6. (Cancelled)

7. (Currently amended) A vehicle mounted terminal <u>that is mounted on a vehicle</u> comprising:

a menu screen obtaining unit configured to obtain a menu screen including pieces of link information each associated with different linked servers interconnected with a wireless network;

a connection status checking unit configured to check the eurrent connection status of each linked server specified by an individual piece of link information included within the menu screen when a component of the vehicle mounted terminal determines that a predetermined condition associated with the running state and/or current location of a vehicle on which the vehicle mounted terminal is mounted has been satisfied, the current connection status indicating whether the corresponding linked server is wirelessly accessible or not by the vehicle mounted terminal; and

a menu screen display processing unit configured to display the eurrent connection status of each linked server specified by a respective piece of link information only included within a subset the pieces of link information checked by the connection status checking unit on the menu screen, each piece of information of the subset of the pieces of link information is associated with an accessible linked server; and

a terminal controller configured to monitor for a plurality of predetermined vehicle conditions of the vehicle on which the vehicle mounted terminal is mounted, wherein when the terminal controller determines that one of the plurality of predetermined vehicle conditions has been satisfied, the terminal controller directs the connection status checking unit to recheck the

connection status of each of the linked servers and the menu screen display processing unit to then display the up-to-date connection status of each of the linked servers such that user selection of a linked server that has become inaccessible due to a change in at least one of the plurality of predetermined vehicle conditions can be avoided.

- 8. (Currently amended) A vehicle mounted terminal according to Claim 7, wherein the <u>a</u> predetermined <u>vehicle</u> condition <u>that triggers rechecking the connection status of each of the linked servers associated with the running state and/or current location of the vehicle is determined to be satisfied when the speed of the vehicle detected by a vehicle-speed determining unit of the vehicle changes and crosses a predetermined value.</u>
- 9. (Currently amended) A vehicle mounted terminal according to Claim 7, further comprising a communication processing unit for receiving image and/or audio information transmitted from the at least one linked server through radio waves,

wherein the <u>a</u> predetermined <u>vehicle</u> condition <u>that triggers rechecking the connection</u> <u>status of each of the linked servers</u> <u>associated with the running state and/or current location of the vehicle</u> is satisfied when the electric field strength of the radio waves carrying the image and/or audio information received by the communication processing unit is determined to have changed and crossed a predetermined reference value by an electric-field strength determining unit of the vehicle mounted terminal.

10. (Currently amended) A vehicle mounted terminal according to Claim 7, further comprising a communication medium determining unit for determining a change of (1) a communication medium or (2) a communications mode, the change of communication medium comprising a change between a wireless Local Area Network (LAN) and a mobile telephone by which data is wirelessly received by the vehicle mounted terminal, and a change of

communications mode comprising a change of communication bands by which data is wirelessly received by the vehicle mounted terminal,

wherein the a predetermined vehicle condition that triggers rechecking the connection status of each of the linked servers associated with the running state and/or current location of the vehicle is satisfied when the communication medium determining unit determines that the communication medium or communications mode of wireless communications of the vehicle mounted terminal has changed.

11. (Currently amended) A vehicle mounted terminal according to Claim 7, further comprising a geographic condition determining unit for determining geographic conditions of a driving location of a vehicle upon which the vehicle mounted terminal is mounted, the geographic conditions of the driving location determinable by the geographic condition determining unit include identified high-rise areas, low-rise residential areas, or mountainous areas,

wherein the <u>a</u> predetermined <u>vehicle</u> condition <u>that triggers rechecking the connection</u>

<u>status of each of the linked servers</u> associated with the running state and/or current location of

the <u>vehicle</u> is satisfied when the <u>type of</u> geographic conditions <u>area</u> determined by the geographic condition determining unit changes.

12. (Currently amended) A vehicle mounted terminal according to Claim 7, further comprising a road determining unit for determining the type of road on which a vehicle, on which the vehicle mounted terminal is mounted, is running, types of road determinable by the road determining unit including expressways, highways, or other types of road,

wherein the <u>a</u> predetermined <u>vehicle</u> condition <u>that triggers rechecking the connection</u>

<u>status of each of the linked servers</u> <u>associated with the running state and/or current location of the vehicle</u> is satisfied when the type of road determined by the road determining unit changes.

13. (Currently amended) A vehicle mounted terminal according to Claim 7, further comprising (1) a communication status determining unit for determining communication status, the communication status indicating a level of signal reception for an accessible linked server, and (2) a communication status history storing unit for storing the history of the determined communication status,

wherein the <u>a</u> predetermined <u>vehicle</u> condition <u>that triggers rechecking the connection</u>

<u>status of each of the linked servers</u> <u>associated with the running state and/or current location of the vehicle</u> is satisfied when the past communication status corresponding to the driving location of a vehicle is determined to be unfavorable based upon the communication status history stored within the communication status history storing unit.

- 14. (Previously presented) A vehicle mounted terminal according to Claim 7, wherein the menu screen has a displayable area larger than a display, and the connection status checking unit checks the connection status of each piece of link information included within the entire menu screen which can be selectively displayed in the display by scrolling or page change.
- 15. (Original) A vehicle mounted terminal according to Claim 7, further comprising a function of a computer which can be connected to the Internet,

wherein the menu screen obtaining unit receives the menu screen through the Internet.

16. (Original) A vehicle mounted terminal according to Claim 7, wherein information transmitted from the linked server includes music data.

17. (Currently amended) A vehicle mounted terminal according to Claim 7, further comprising a function of a receiver for receiving information distributed from a broadcast station,

wherein the menu screen obtaining unit retrieves the menu screen stored within a storage device incorporated in the receiver, the receiver being located on a the vehicle.

18. (Currently amended) A method for displaying a menu screen, comprising:

displaying a menu screen on a <u>vehicle mounted</u> terminal <u>that is</u> mounted on a vehicle, the menu screen including pieces of link information associated with linked servers interconnected with a network, the linked servers may or may not be accessible by the <u>vehicle mounted</u> terminal mounted on the vehicle depending upon driving state and/or driving location of the vehicle, the pieces of linked information being displayed on the menu screen depending upon a connection status of the corresponding linked server;

checking a current connection status of each linked server specified by the pieces of link information included within the menu screen when (1) the vehicle is traveling and (2) the terminal automatically determines that a predetermined condition that is a function of driving state and/or driving location of the vehicle has been satisfied, the current connection status indicating whether radio waves carrying image and/or audio data originating from a corresponding linked server are currently wirelessly accessible or not by the vehicle mounted terminal; and

reflecting <u>displaying</u> on the menu screen the checked current connection status of only the linked servers in relation to corresponding pieces of link information included within a subset of the pieces of link information, wherein the subset of the pieces of link information <u>that</u> are associated with accessible linked servers and, while pieces of link information that are associated with inaccessible linked servers are <u>not</u> displayed on the menu screen;

monitoring for predetermined vehicle conditions of the vehicle on which the vehicle

mounted terminal is mounted;

rechecking the connection status of each linked server when a predetermined vehicle condition has been detected; and

updating the menu screen on the vehicle mounted terminal to display only pieces of link information that are associated with linked servers that are currently accessible via the vehicle mounted terminal based upon rechecking the connection status of each linked server in response to the predetermined vehicle condition being detected such that user selection of a linked server that is currently inaccessible from the vehicle mounted terminal can be avoided.

- 19. (Currently amended) A method according to Claim 18, wherein the predetermined vehicle condition is determined to be satisfied when it is determined that the vehicle enters a different type of geographic area by the terminal when a connection status of any linked server changes.
- 20. (Currently amended) A method according to Claim 18, wherein information transmitted from an accessible linked server includes music data and the predetermined condition is determined to be repeatedly satisfied when it is determined that a type of road upon which the vehicle is traveling changes by the terminal whenever another timing interval has elapsed.
- 21. (New) A vehicle mounted terminal comprising: a terminal controller comprising:

a menu screen obtaining unit configured to obtain a menu screen including pieces of link information for display on the menu screen, wherein each piece of link information corresponds to a server interconnected with a wireless network;

a connection status checking unit configured to determine a connection status of each server respectively specified by the pieces of link information included within the menu screen, the connection status indicating whether an individual server is wirelessly accessible or not from the vehicle mounted terminal; and

a display processing unit configured to visually indicate whether each server associated with a piece of link information displayed on the menu screen is accessible based on the respective connection status determined;

wherein the terminal controller is configured to monitor for predetermined vehicle events associated with a vehicle on which the vehicle mounted terminal is mounted that impact the connection status of one or more server, and

when a predetermined vehicle event is detected, the terminal controller directs the connection status checking unit to recheck the connection status of each server, and

if the connection status of a server previously accessible via the vehicle mounted terminal has changed to being inaccessible, the terminal controller updates the menu screen to reflect that the previously accessible server is currently inaccessible via the vehicle mounted terminal such that user selection of a corresponding piece of link information can be avoided.

- 22. (New) A vehicle mounted terminal of claim 21, wherein one of the predetermined vehicle events monitored for by the terminal controller, and at which the connection status of each server is rechecked, is speed of a vehicle in which the vehicle mounted terminal is mounted increasing about a reference speed.
- 23. (New) A vehicle mounted terminal of claim 21, wherein one of the predetermined vehicle events monitored for by the terminal controller, and at which the connection status of each server is rechecked, is that a type of road on which a vehicle, in which the vehicle mounted terminal is mounted, is traveling changes.

- 24. (New) A vehicle mounted terminal of claim 21, wherein one of the predetermined vehicle events monitored for by the terminal controller, and at which the connection status of each server is rechecked, is that a geographic condition of an area through which a vehicle, in which the vehicle mounted terminal is mounted, is traveling changes.
- 25. (New) A vehicle mounted terminal of claim 21, wherein one of the predetermined vehicle events monitored for by the terminal controller, and at which the connection status of each server is rechecked, is that a electric-field strength of received radio waves crosses a predetermined reference value.
- 26. (New) A vehicle mounted terminal of claim 21, wherein one of the predetermined vehicle events monitored for by the terminal controller, and at which the connection status of each server is rechecked, is that an available communication speed crosses a reference value.